

TIDAL POWER SPECIAL UHPD 5W-30

Synthetic MID-SAPS Heavy Duty Diesel Engine oil

TIDAL POWER SPECIAL UHPD 5W-30 is a fuel conserving super high performance MID SAPS oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and running on low Sulphur Diesel Fuel (max. 50 ppm). This product is formulated for use in Euro-5 and Euro-6 engines equipped with Diesel Particulate Filter (DPF). This product is also suitable for vehicles equipped with EGR and/or SCR after treatment systems.

TIDAL POWER SPECIAL UHPD 5W-30 is formulated on high refined synthetic base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals up to 150.000 km.
- Fuel conserving.

TIDAL POWER SPECIAL UHPD 5W-30 meets the following performance criteria:

Approved:	MB-Approval 228.51	MAN M3677 - 3775	Scania LDF-4 (Pending)
	Volvo VDS-4.5	Mack EOS-4.5	Renault VI RLD-3
Meets:	ACEA E4/E6/E7/E9	MB 228.52 / 228.31	API CK-4
	Deutz DQC IV-18 LA	MTU Type 3.1 / 2.1	MAN M3777
	MAN M3691	Volvo VDS-4	Rengult VI RLD-4

JASO DH-2 Cummins CES 20086 Cummins CES 20081

CAT ECF-3 DDC 93K222 DCC 93K218

Typical Analysis

Properties	Unit	Method	Typical Value	
SAE Grade		SAE J300	5W-30	
Density @15°C	kg/m³	ASTM 4052	855	
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D704	2 68	
Kinematic Viscosity @ 100°C	mm²/s	ASTM D704	2 11.8	
Viscosity Index		ASTM D227	70 170	
Viscosity CCS @ -30°C	сР	ASTM D529	6100	
Flash Point COC	°C	ASTM D92	>201	
Pour Point	°C	ASTM D734	6 -42	
Total Base Number	mgKOH/g	ASTM D289	ASTM D2896 13.2	
Sulphated Ash	%Wt	ASTM D874	ASTM D874 0.98	
Date Issued: 14-3-2022	Supersedes: 12-11-2021 Revision Nr.:		Revision Nr.: 06	















