

## **STREAM POWER 4T 10W-50**

### **Semi-Synthetic 4-Stroke Motorcycle Oil**

**STREAM POWER 4T 10W-50** is a semi synthetic 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

**STREAM POWER 4T 10W-50** is based on high-quality mineral and synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding thermo-oxidative stability.
- Exceptional anti-wear, anti-rust and anti-corrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature-high shear environment.
- Provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures.
- Ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

**STREAM POWER 4T 10W-50** meets the following performance criteria:

API SL            JASO MA-2

### **Typical Analysis**

| <b>Properties</b>           | <b>Unit</b>            | <b>Method</b>    | <b>Typical Value</b> |
|-----------------------------|------------------------|------------------|----------------------|
| SAE Grade                   |                        | SAE J300         | 10W-50               |
| Density @15°C               | kg/m <sup>3</sup>      | ASTM 4052        | 856                  |
| Kinematic Viscosity @ 40°C  | mm <sup>2</sup> /s     | ASTM D7042       | 120                  |
| Kinematic Viscosity @ 100°C | mm <sup>2</sup> /s     | ASTM D7042       | 18.1                 |
| Viscosity Index             |                        | ASTM D2270       | 169                  |
| Flash Point COC             | °C                     | ASTM D92         | 201                  |
| Pour Point                  | °C                     | ASTM D7346       | -34                  |
| Total Base Number           | mgKOH/g                | ASTM D2896       | 8.5                  |
| Date Issued: 16-6-2021      | Supersedes: 21-03-2016 | Revision Nr.: 01 |                      |

