

## STREAM POWER OTB 2T

### 2-Stroke Outboard Engine Oil

**STREAM POWER OTB 2T** is a high performance ashless 2-stroke engine oil to meet the most critical requirements of the latest outboard and snow mobile engines. It exceeds the stringent performance requirements of the National Marine Manufacturers Association's specification NMMA TC-W3®.

**STREAM POWER OTB 2T** is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent lubricity.
- Protection against wear and rust.
- High protection against scuffing and deposit forming.
- Easy mixing and stable mixture even at low temperatures

**STREAM POWER OTB 2T** meets the following performance criteria:

NMMA TC-W3

### Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m <sup>3</sup>	ASTM 4052	873
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	45.79
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	7.0
Viscosity Index		ASTM D2270	117
Flash Point COC	°C	ASTM D92	>100
Pour Point	°C	ASTM D7346	-35
Total Base Number	mgKOH/g	ASTM D2896	8.8
Date Issued: 16-6-2021	Supersedes: 24-03-2016	Revision Nr.: 01	

