

AUTOGEAR POWER MP 85W-90

Automotive Gear Oil

AUTOGEAR POWER MP 85W-90 is a high-performance gear lubricant for use in heavy duty manual transmissions and axle drives of commercial vehicles and passenger cars.

AUTOGEAR POWER MP 85W-90 is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR POWER MP 85W-90 meets the following performance criteria:

API GL-5 MB 235.0 MIL-L-2105D MAN 342 M1
Volvo 97310 Volvo 97316 Voith 3.325-339
ZF TE-ML 07A, 08, 16B/C/D, 17B, 19B, 21A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	85W-90
Density @15°C	kg/m ³	ASTM 4052	890
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	1674
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	17.1
Viscosity Index		ASTM D2270	105
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-26
Date Issued: 22-01-2021		Supersedes: 25-03-2016	Revision Nr.: 01

