

## **AUTOGEAR POWER SYN 75W-85**

**Fully Synthetic Universal Transmission Oil** 

**AUTOGEAR POWER SYN 75W-85** is an universal high performance fuel saving transmission on synthetic technology for use in manual shifted transmission of the modern passenger car and light vans where an API GL-5 is recommended.

**AUTOGEAR POWER SYN 75W-85** is based on special selected high performance synthetic base oil in combination with a special selected EP-additive package to reach to following properties:

- Excellent extreme pressure properties
- Excellent thermal- and oxidation stability
- Good shifting even at low temperatures
- Low pour point
- Fuel saving properties
- Excellent protection against the forming of foam, corrosion and wear

## **AUTOGEAR POWER SYN 75W-85** meets the following performance criteria:

API GL-5 MB 235.7 ZF TE-ML 18 VW G 052 190

VW G 055 190 Alfa-Romeo BMW Fiat Lancia

## **Typical Analysis**

Properties	Unit	Method		Typical Value	
SAE Grade		SAE J306		75W-85	
Density @15°C	kg/m³	ASTM 4052		862	
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042		78.55	
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042		12.5	
Viscosity Index		ASTM D2270		160	
Brookfield Viscosity @-40°C	сР	ASTM D2983		150000	
Flash Point COC	°C	ASTM D92		>201	
Pour Point	°C	ASTM D7346		-60	
Date Issued: 16-6-2021	Supersedes: 11	Supersedes: 11-10-2016		Revision Nr.: 01	















