

SLIDEWAY POWER 32

Slideway Oil

SLIDEWAY POWER 32 is a superior quality lubricant specially developed to meet the requirements of modern high production machine tool slideways.

SLIDEWAY POWER 32 is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Low frictional properties reduce chatter and stick-slip of slides and ways.
- Improved surface finish and dimensional accuracy of workpieces.
- Excellent demulsibility provides ready separation from soluble cutting fluids.
- Prolonged coolant life and reduced cost of replacement and disposal.
- Superior metal wetting properties and adhesiveness resist wash-off from critical surfaces and protect from attack of high pH coolants.
- Good filterability provides easy circulation through filters and reduces stick-slip, chatter and wear.
- Excellent anti-wear performance provides high levels of protection for gears, bearings and slides.
- Effective rust and corrosion inhibitors provide enhanced protection of machine tool slides even in presence of aqueous cutting fluids.
- Good thermal and oxidative stability.

SLIDEWAY POWER 32 meets the following performance criteria:

ISO 19378 GA & GB
DIN 51524 part II
AIST 224

General Motors LS2
DIN 51517 part III
AGMA 9005 E02 (EP)

ISO 11158 HG
FZG 12

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Class			32
Density @15°C	kg/m ³	ASTM 4052	872
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	33.2
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	5.4
Viscosity Index		ASTM D2270	102
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
FZG Fail Load Stage, min		DIN 51354-2	12
Total Acid Number	mgKOH/g	ASTM D974	0.5
Date Issued: 15-6-2021		Supersedes: 04-04-2018	Revision Nr.: 02

