

LUNA GREASE EPHT 2

Agriculture & Industrial Grease

LUNA GREASE EPHT 2 is a high performance bentone clay thickened grease suitable for both industrial and automotive applications.

LUNA GREASE EPHT 2 is a high quality multipurpose grease that can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain and rolling bearings.

LUNA GREASE EPHT 2 is a lithium thickened lubricating grease based on mineral oil. The grease contains corrosion inhibitors and EP additives to ensure the following properties:

- Non-Melting point.
- Suited for application with a very wide temperature range.
- Special applications at elevated temperatures.

LUNA GREASE EPHT 2 meets the following performance criteria:

DIN 51502 ISO 6743 KP2N-20 ISO-L-XCDAB-2

Typical Analysis

Properties	Unit	Method	Typical Value
NLGI Grade		ASTM D 217 mod	2
Thickener			Clay
Base oil			Mineral
Colour		Visual	Brown
Dropping Point	°C	IP 396	N/A
Base oil viscosity at 40 °C	mm ² /s	ASTM D 7152	475
Penetration 60 strokes		ISO 2137	265-295
Working temperature	°C		-30 to +150
Date Issued: 10-6-2021		Supersedes: 19-04-2017	Revision Nr.: 01

